

SDS Inventory Manager in use

How to create Secondary container labels for hazardous chemicals

A secondary label is used on smaller containers, such as spray bottles, jugs, or jars that chemicals are transferred to from the primary container once within the workplace. It contains information about the products, such as its ingredients and nutritional values, health and safety warnings, instructions for use, manufacturer/supplier and contact information, or detailed tracking and product information in a barcode format.

According to OSHA, secondary containers need to comply with the labeling requirements.

On the label icon, you can generate Secondary Container labels.

Click here to [open SDS Manager to create Secondary container labels \(require login\)](#).

Product Name ↑	Supplier Name	Location	Signal word	Pictograms & Controls	Substance hazard H S E	Actions
1,2-Dichlorobenzene	AccuStandard, Inc	Hazardous Area	Warning		H4 S1 E1	

The label has respective QR codes to view the actual SDS file and track chemical usage and disposal.

Icons from the SDS, Hazard statements and Prevention statements are also shown in the label.

SDS Inventory Manager in use

The screenshot shows the SDS Inventory Manager interface. On the left, a dropdown menu is open, displaying various label formats: A4 (8.5"x11"), A5 (5.5"x8.5"), A6 (4"x6"), A7 (3"x4"), 2"x4", A8 (2"x3"), A9 (1.5"x2"), 1"x2", and A10 (1"x1.5"). The A4 (8.5"x11") option is highlighted with a red border. On the right, a preview of a label for "3-D Laserscanning Cleaner Spray" is shown. The label includes a QR code, a PDF icon, and a Track Usage icon. The label text is as follows:

3-D Laserscanning Cleaner Spray
Company Name: Helling GmbH
Signal Word: Danger

Hazard Statements
H222: Extremely flammable aerosol;
H229: Pressurized container: may burst if heated;
H319: Causes serious eye irritation;
H336: May cause drowsiness or dizziness

Precautionary Statements
P102: Keep out of reach of children.;
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.;
P211: Do not spray on an open flame or other ignition source.;
P251: Do not pierce or burn, even after use.;
P271: Use only outdoors or in a well-ventilated area.;
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.;
P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Ingredients:


EC/CAS	Chemical Name	Concentration
200-661-7/67-63-0	Isopropanol	70 - 80 %
200-661-7/106-97-8	Butane	15 - 20 %
203-448-7/74-98-6	Propane	6 - 10 %

Supplier Name: Helling GmbH

Emergency Contact: Poison Control Center
Emergency Telephone: 800-222-1222

When smaller formats are chosen, less information is displayed on the label due to the size constraints. Below is an example of a 2" label that can be printed on a Dymo sticker printer.

SDS Inventory Manager in use



SDS Manager fully supports all major Avery label formats. When printing to Avery labels, you can easily choose which specific label position on the sheet you'd like to use, ensuring efficient and flexible printing.


SDS Inventory Manager in use

Print Label ✕




Product information Edit HMIS information 📱 🖨️ Print Label

A4 (297x210mm)
A5 (148x210mm)
A6 (105x148mm)
A7 (105x74mm)
52x105mm
50x105mm
A8 (52x74mm)
50x74mm
A9 (37x52mm)
26x52mm
A10 (26x37mm)
Brady & Avery label
4" x 3 1/3" (6 per page) - Avery 5164 / 5264
8 1/8" x 5" (2 per page) - Avery 6573
8 1/2" x 11" (1 per page) - Avery 5255
4" x 6" (1 per page) - Avery 5292
4" x 2" (10 per page) - Avery 5163 / 8163 / 60505
2 5/8" x 1" (30 per page) - Avery 5160
2" x 2" (12 per page) - Avery 60506
3 1/2" x 5" (4 per page) - Avery 60503
2 1/2" x 1" (24 per page) - Avery 60517
6" x 3" (1 per page) - DuraLabel Pro 300
6" x 4" (1 per page) - Brady BBP31

AATREX LIQUID 480
Company name: Syngenta Canada Inc
Signal word: Warning



Hazard statements • Precautionary statements
H373, P260, P314, P501



Only use in ventilated areas

HEALTH	2
FLAMMABILITY	2
PHYSICAL HAZARD	2
PERSONAL PROTECTION	2

Unique solution ID: #1051

Author: n/a

Last update: 2024-10-24 15:53