

Daily use

How to create Secondary container labels for hazardous chemicals

A secondary label is used on smaller containers, such as spray bottles, jugs, or jars that chemicals are transferred to from the primary container once within the workplace. It contains information about the products, such as its ingredients and nutritional values, health and safety warnings, instructions for use, manufacturer/supplier and contact information, or detailed tracking and product information in a barcode format.

According to OSHA, secondary containers need to comply with the labeling requirements.

On the label icon, you can generate Secondary Container labels.

Click here to [open SDS Manager to create Secondary container labels \(require login\)](#).

| Product Name ↑ | Supplier Name | Location | Signal word | Pictograms & Controls | Substance hazard H S E | Actions |
|---------------------|-------------------|----------------|-------------|-----------------------|---------------------------|---------|
| 1,2-Dichlorobenzene | AccuStandard, Inc | Hazardous Area | Warning | | | |

The label has respective QR codes to view the actual SDS file and track chemical usage and disposal.

Icons from the SDS, Hazard statements and Prevention statements are also shown in the label.

Daily use

A4 (8.5"x11")

A4 (8.5"x11")

A5 (5.5"x8.5")

A6 (4"x6")

A7 (3"x4")

2"x4"

A8 (2"x3")

A9 (1.5"x2")

1"x2"


A10 (1"x1.5")

Use standard statement description


1 / 1 | - 67% + | [] []

3-D Laserscanning Cleaner Spray

Company Name: Helling GmbH
Signal Word: Danger



View PDF




Track Usage

Hazard Statements

H222: Extremely flammable aerosol;
H229: Pressurized container: may burst if heated;
H319: Causes serious eye irritation;
H336: May cause drowsiness or dizziness

Precautionary Statements

P102: Keep out of reach of children.;
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.;
P211: Do not spray on an open flame or other ignition source.;
P251: Do not pierce or burn, even after use.;
P271: Use only outdoors or in a well-ventilated area.;
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.;
P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.



Ingredients:

| EC/CAS | Chemical Name | Concentration |
|--------------------|---------------|---------------|
| 200-661-7/67-63-0 | Isopropanol | 70 - 80 % |
| 200-661-7/106-97-8 | Butane | 15 - 20 % |
| 203-448-7/74-98-6 | Propane | 6 - 10 % |

Supplier Name: Helling GmbH

Emergency Contact: Poison Control Center
Emergency Telephone: 800-222-1222

When smaller formats are chosen, less information is displayed on the label due to the size constraints. Below is an example of a 2" label that can be printed on a Dymo sticker printer.

Daily use

The screenshot displays the SDS Manager interface. On the left, a 'Print format' dropdown menu is open, listing various Avery label sizes: 2"x4", A4 (8.5"x11"), A5 (5.5"x8.5"), A6 (4"x6"), A7 (3"x4"), 2"x4" (highlighted with a red border), A8 (2"x3"), A9 (1.5"x2"), 1"x2", and A10 (1"x1.5"). The main content area shows a label for '3-D Laserscanning Cleaner Spray' by Helling GmbH. The label includes two QR codes (labeled 'View PDF' and 'Track Usage'), hazard statements (H222, H229, H319, H336, P102, P210, P211, P251, P271, P305+P351+P338, P410+P412), and a signal word 'Danger'. Below the text are several hazard pictograms: a flame, an exclamation mark, a hand being washed, a flame over a hand, a person wearing eye protection, a person wearing a respirator, a hand being washed, and a document with a checkmark.

SDS Manager fully supports all major Avery label formats. When printing to Avery labels, you can easily choose which specific label position on the sheet you'd like to use, ensuring efficient and flexible printing.


Daily use

Print Label



Print Label

Product information Edit HMIS information Print Label

AATREX LIQUID 480
Company name: Syngenta Canada Inc
Signal word: Warning



Hazard statements • Precautionary statements
H373, P260, P314, P501



Only use in ventilated areas

Unique solution ID: #1051

Author: n/a

Last update: 2024-10-24 15:53