

SDS Inventory Manager in use













How to create Secondary container labels for hazardous chemicals

A secondary label is used on smaller containers, such as spray bottles, jugs, or jars that chemicals are transferred to from the primary container once within the workplace. It contains information about the products, such as its ingredients and nutritional values, health and safety warnings, instructions for use, manufacturer/supplier and contact information, or detailed tracking and product information in a barcode format.

According to OSHA, secondary containers need to comply with the labeling requirements.

On the label icon, you can generate Secondary Container labels.

Click here to [open SDS Manager to create Secondary container labels \(require login\)](#)

Product Name ↑	Supplier Name	Location	Signal word	Pictograms & Controls	Substance hazard H S E	Actions
1,2-Dichlorobenzene	AccuStandard, Inc	Hazardous Area	Warning	 	  	      

The label has respective QR codes to view the actual SDS file and track chemical usage and disposal.

Icons from the SDS, Hazard statements and Prevention statements are also shown in the label.

SDS Inventory Manager in use


A4 (8.5"x11")
A4 (8.5"x11")
A5 (5.5"x8.5")
A6 (4"x6")
A7 (3"x4")
2"x4"
A8 (2"x3")
A9 (1.5"x2")
1"x2"
A10 (1"x1.5")


Use standard statement description

1 / 1 | - 67% + | [icon] [icon]

3-D Laserscanning Cleaner
Spray



Company Name: Helling GmbH
Signal Word: Danger









View PDF


Track Usage

Hazard Statements
H222: Extremely flammable aerosol;
H229: Pressurized container: may burst if heated;
H319: Causes serious eye irritation;
H336: May cause drowsiness or dizziness

Precautionary Statements
P102: Keep out of reach of children.;
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.;
P211: Do not spray on an open flame or other ignition source.;
P251: Do not pierce or burn, even after use.;
P271: Use only outdoors or in a well-ventilated area.;
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.;
P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.



Ingredients:

EC/CAS	Chemical Name	Concentration
200-661-7/67-63-0	Isopropanol	70 - 80 %
200-661-7/106-97-8	Butane	15 - 20 %
203-448-7/74-98-6	Propane	6 - 10 %

Supplier Name: Helling GmbH

Emergency Contact: Poison Control Center
Emergency Telephone: 800-222-1222


When smaller formats are chosen, less information is displayed on the label due to the size constraints. Below is an example of a 2" label that can be printed on a Dymo sticker printer.

Page 2 / 3

© 2024 SDS Manager <eb@aston.no> | 2024-05-16 17:04

URL: <https://faq.sdsmanager.com/content/26/243/en/how-to-create-secondary-container-labels-for-hazardous-chemicals.html>

SDS Inventory Manager in use



Unique solution ID: #1051

Author: n/a

Last update: 2024-05-14 11:32