

SDS Inventory Manager in use


How do I get alerted about new revisions of SDS and how do I upgrade to the latest version?

New revisions of SDSs are issued every 1 to 3 years.

New revisions are issued because of new regulatory requirements, corrections or new discoveries by the suppliers. Users of chemicals are required to have the latest version of the SDS in their library.

SDS Manager are continuously crawling thousands of supplier websites for new revisions of safety data sheets and add them to our database.

When you use SDS manager, you will be alerted when we find new versions of SDSs in your library. In the header bar of SDS Manager, you will see the alert icon showing the number of outdated SDSs you have in your library. In the example below, we have 35 outdated SDSs that need to be updated.





When you click on the notification bell, you will be directed to ["SDS where newer version exists" page](#) where we will list SDSs you have in your library for which we found newer versions.

Click here to [open SDS Manager to review SDS where newer version exists \(require login\)](#)








Product Name	Product Code	Revision date	Revision date newer version	Locations		
MELMENT F 10		2018-08-20	→ 2020-01-15	Lab B	Diff.	Upgrade to new version
Navistar Fleetrite Diesel Exhaust Fluid	FLTFP (2.5 Gal); FLTFQ (55 Gal); FLTFR (275 Gal); FLTFS (330 Gal)	2012-03-26	2018-06-01	Lab E	Diff.	Upgrade to new version

Click on the "Diff." button to see side-by-side changes between the SDS you are currently using and the new version.

SDS Inventory Manager in use

Changed values		Current version	New version
			
Emergency telephone			+1 973 245-6000
Health risk	1		4
Safety risk	1		4
Revision date	2018-08-20		2020-01-15
Environment risk	1		4
Section 3: composition/information on ingredients		According to Regulation 2012 OSHA Haz CAS Number 50-00-0 Weight % < 0.1%	According to Regulation 2012 OSHA Haz Formaldehyde CAS Number: 50-00-0 Content (W/W): < 0.1% Synonym: Formaldehyde; Forma
First-aid measures after ingestion		Rinse mouth immediately and then drink plenty of water, seek medical attention. Do not induce vomiting unless told to by a poison control center or doctor.	Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention. Do not induce vomiting unless told to by a poison control center or doctor.

You can choose to upgrade one SDS at a time (1) or upgrade all SDSs to the latest version in one operation (2).



SDS where newer version exists

Refresh all cached SDS values

Upgrade all SDS to latest version

SDS status

Locations

Only list SDS in use

List SDS on all locations

Product Name	Product Code	Revision date	Revision date newer version	Locations	
MELMENT F 10		2018-08-20	2020-01-15	Lab B	<div>Diff.</div> <div>Upgrade to new version</div>
Navistar Fleetrite Diesel Exhaust Fluid	FLTFP (2.5 Gal); FLTFQ (55 Gal); FLTFR (275 Gal); FLTFS (330 Gal)	2012-03-26	2018-06-01	Lab E	<div>Diff.</div> <div>Upgrade to new version</div>

Unique solution ID: #1090
Author: n/a
Last update: 2023-08-12 18:21